



780-054HD

Description:

Half Surface > Door of Any Material - Heavy Duty



- | | |
|---|--|
| <p>Clearance - 5/32" (4 mm) minimum recommended hinge side</p> <p>- Plus standard lockside clearance</p> <p>- Refer to Door and Frame Dimensioning in the General Information section for further details</p> <p>Fasteners - Dril-Kwik (R) screws and Sex bolts</p> <p>Length Options - Standard and Custom</p> <p>Door Reinforcement - None required</p> | <p>Frame Reinforcement - None required to 200 lbs. Heavier weight use 16-gauge channel.</p> <p>Fire Rating - Up to 3 hr. metal and 90 min. wood composite (with studs)</p> <p>Special Features - Security molding</p> <p>- Frame leaf alignment rib for proper hinge location</p> <p>- 1/8" (3 mm) inset</p> <p>Warranty - All Roton products have a lifetime warranty. When ordering electric Roton, the electric portion of the hinge has a one-year warranty.</p> |
|---|--|

Roton Model	Length (inches)	Length (cm)	Hole Count (Door)	Hole Count (Jamb)
780-054HD	79	200.7	8	15
780-054HD	83	210.8	8	19
780-054HD	85	215.9	8	19
780-054HD	95	241.3	9	19
780-054HD	119	302.3	10	21

