



**UL 752 Specifications & Ammunition**

Rating	Ammunition	Grain	(g)	Minimum fps	Velocity m/s	shots fired	paragraph	thickness	lb/sq. ft.
SecureAll Level 1	9mm full metal copper jacket with lead core	124	8	1175	358	3	4.3	1/4"	2.6
SecureAll Level 2	.357 Magnum jacketed lead soft point	158	10.2	1250	381	3	4.4	5/16"	3.6
SecureAll Level 3	.44 Magnum lead semi wad-cutter	240	15.6	1350	411	3	4.5	7/16"	4.9
SecureAll Level 4	.30 caliber rifle lead core	180	11.7	2540	774	1	4.6	1 3/8"	14
SecureAll Level 5	7.62mm rifle lead core full metal copper jacket military ball	150	9.7	2750	838	1	4.7	1 7/16"	14.9
Secure All Level 6	9mm fullet metal copper jacket with lead core	124	8	1400	427	5	4.8	3/8"	3.9
SecureAll Level 7	5.56mm rifle full metal copper jacket with lead core	55	3.56	3080	939	5	4.9	1 1/8"	11.9
SecureAll Level 8	7.62mm rifle lead core full metal copper jacket military ball	150	9.7	2750	838	5	4.1	1 7/16"	14.9
Supplementary Shotgun	12-gauge rifled lead slug	437	28.3	1585	483	3	4.11		
	12-gauge 00 lead buck shot (12 pellets)	650	42	1200	366				

**Maximum velocity is 110% of minimum vleocity.**

Paragraphs are listed in "UL 752 Paragraphs" page.

Note: When printing, be sure to print in *Landscape* mode for best results.

Protective Structures, Ltd.  
 7565 Industrial Court  
 Alpharetta, Georgia 30004  
[www.protectivestructures.com](http://www.protectivestructures.com)  
[info@protectivestructures.com](mailto:info@protectivestructures.com)

770.521.8666 phone  
 770.521.2299 fax

